

ETATRACK active 1500

LORENTZ 

Available From:



Active Solar Tracking System

Characteristics

- total module surface up to 15 m²
- maintenance-free
- high reliability and life expectancy
- low power consumption, ca. 1.25 kWh/year
- no unnecessary tracking movements
- no failure prone light sensor
- designed to withstand wind speed up to 150 km/h
- cost-efficient tracking system

Application

Single-axis solar tracking increases the energy return of solar modules by 25 to 35 % per year in average, dependent on location, respectively up to 55 % during summer months.

Tracking


- angle East-West: 90°, active
- elevation angle: 0° - 45°, manually adjustable
- no separate sensors, it uses the modules as sensor
- energy supply of tracking drive: 12 V nominal, max. 200 V (Voc), provided by one of the tracked modules
- horizontal position at night
- tracking in steps according to the daily sunshine duration

Module Surface And Fixation

- 15 m² total module surface (up to 2.4 kWp, dependent on module type)
- fixation: movable stainless steel clips, fitting for most module types; no drilling of additional holes into the module frame

Mounting And Foundation

- mounting pole: length 2.75 m
- surface concrete foundation (approx. 3.0 m²)



Included In Delivery

- frame and fixation elements made of steel, Zn-coated, stainless steel clips for modules
- electronics incl. battery in plastic housing
- linear motor
- mounting pole

DIY System

- Do It Yourself and cut cost with the DIY kit
- includes all fixation elements made of Zn-coated steel, stainless steel clips for modules, ETATRACK Control and a heavy duty linear drive

TWIN System

- one controller operates two trackers
- DIY kits available

example of system dimensions for 12 x module BP 4170 (2,040 Wp)